



Technical data sheet for

SINGLE PAN ELECTRIC FRYER 450mm

E43E

- 17kW high performance single pan fryer
- Digital display temperature control with 3 product timers
- Easy clean stainless steel open pan with 10 year limited warranty
- 27L oil capacity
- 32mm (1 ¹/₄") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service

Fully modular



Overall Construction

- Stainless steel pan
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Hinge out counterbalanced heating elements
- \bullet 32mm (1 $^{1}/_{4}$ ") drain valve
- 63mm dia. heavy-duty 1.2mm 304 stainless steel adjustable legs at front and two rollers at rear
- 2 baskets and stainless steel lid supplied standard

Controls

- Digital display electronic thermostat
- Thermostat range 88-193°C
- 3 programmable product timers with countdown display and alarms
- \bullet Straight or compensating temperature cook time control
- Heating and basket drop displays
- Programmable melt cycles
- Fail-safe over-temperature safety cut-out
- Element tilt switch for heating cut-out on element lift

Cleaning and Servicing

- \bullet Open stainless steel pan with hinge out elements for easy clean
- Easy clean basket support bar
- \bullet 32mm (1 $^{1}/_{4}$ ") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all controls from front of unit

CE



Technical data sheet for

SINGLE PAN ELECTRIC FRYER 450mm

Specifications

Production rate

31kg/hr

Pan Size

Oil capacity 27L (50lbs shortening) Width 365mm Length 380mm Oil frying depth 95mm

Baskets

2 chrome plated wire baskets 140mm W x 335mm D x 145mm H

3 x 5.66kW stainless steel heating elements

Electrical requirements

17kW, 400-415Vac, 50/60hz, 3P+N+E

L1 23.6A L2 23.6A L3 23.6A

Dimensions

Width 450mm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight

64kg

Packing data


0.54m3, 105kg Width 870mm Depth 495mm Height 1255mm

Options

Adjustable feet at rear Filtamax Filtration System Extra baskets Side splash guards Joining caps Castors

E43F







OBLUE SEAL

www.blueseal.co.uk www.bluesealevolution.com

United Kingdom

Blue Seal Limited

Unit 67

Gravelly Business Park

Gravelly

Birmingham B24 8TQ

England

Telephone 0121-327 5575

Facsimile 0121-327 9711

Email sales@blue-seal.co.uk

www.blue-seal.co.uk

Australia Moffat Pty Limited

740 Springvale Rd

Mulgrave

Victoria 3170

Australia

Telephone 03-9518 3888

Facsimile 03-9518 3833

Fmail vsales@moffat.com.au

 \bigoplus

www.moffat.com.au

New Zealand Moffat Limited

16 Osborne St

P0 Box 10-001

Christchurch 8011

New Zealand

Telephone 03-389 1007

Facsimile 03-389 1276

Email sales@moffat.co.nz

www.moffat.co.nz



Designed and manufactured by



All Blue Seal products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Printed in China © Copyright Moffat Ltd Moffat/4825-UK/BH/2.5M/12.06



